
The Purest Ingredients only are used, and the utmost Care and Cleanliness exercised in the Manufacture throughout.

Our Registered Telegraphic Address is
"DISPENSARY, HONGKONG."
And all signed messages addressed thus will
reach prompt attention.

LEMONADE
POTASH WATER
SELTZER WATER

GINGERADE

No Credit given for Bottles that look dirt
or greasy, or that appear to have been used for

Hongkong, 26th May, 1890. [2]

The Daily Press

China, the construction of railways in the Empire, and the great augmentation in the volume of the foreign trade of that country.

the population to spread out eastward and westward and to the south, might not, regard be had to the commercial prospects, be deemed unduly sanguine. But

present but also with regard to the requirements and possibilities of the future. He has a scheme in hand to bring

therefore, that the requirements will advance more rapidly than the supply. When the Titam works were entered upon

out, was for the supply of water to 92,000 persons, but the works were not complete until 1889, by which time the population had increased to upwards of 170,000.

"I am of opinion that, considering the limited area of the city and its present

"supply of which is entirely separate from
"that of the city of Victoria. Should suc-
"however, not be the case, a material in-

of the supply from the other reservoirs the
might be calculated to give a supply for
80,000 or 90,000 persons; adding this num-

be obtained from artesian wells, or, failing

we stated erroneously that Captain Hoffman
was wounded in the arm. It was Count Na-
hanna who was injured."

The Points are Oblique Cut, and are in 5 Grades
WAVERLEY, WORKS, EDDYBURN.

state in what manner it will affect the future position of this Company. In the first place for the next ten years to come we will have

bandits, who constantly harass the country; he
with 600 determined men, opening a regular
attack upon the place it was no use to stir

to be of similar construction to one above described and to have a maximum discharging capacity of one million gallons per hour.

construction of the reservoir on the lower part of the work might be undertaken by raising and strengthening the embankment.

